

GENUINE KMAC... ALSO INCLUDES
SEPARATE RADIAL THRUST
BEARINGS FOR STEERING LOADS!
PREVENT SPRING DRAG / BINDING


FULL RACE CAMBER & CASTER Biggest Adjustment Range

(NO FLEX -Tauter / Quicker response times, more effective shock control)

- Extra H/Duty self align spherical bearings (PTFE lined)
- ✓ Fit and can adjust with strut brace
- Fit With or Without Adj. Coil Overs (60-70mm I.D.)
- Centers are Replaceable for virtual lifetime usage
- ✓ Massive (3½") fully sealed thrust bearings

Simply replaces original strut 'upper' mounts

(All items above Coil spring except for OEM dust cover and bump stop)



2. KMAC BUMP STOP
If lowering can cut top
section of bump stop to
increase shock
travel/absorption



Use smaller elastomer Seats 60^{mm} O.D (or 65^{mm} O.D if up to 70^{mm} Coil overs) fitted.

INITIALLY SIT KMAC ADJUSTERS ON TOP OF STRUT TOWERS...

Kit (Centers) are 'Left' and 'Right' hand offsets

THEREFORE BEFORE INSTALLING / ADJUSTING (Select Center hole position that will achieve best results!)

Refer manufacturers workshop manual re removal and installation
Observe all safety procedures



This side showing "CENTER" position

Showing Extra Neg. Camber (and/or Caster)

B. IF INNER TYRE WEAR MOUNT POSITIVE


(+) CAMBER

#193416-3L

KMAC,

And to REAR for Pos. Caster.





ALIGNING

KMAC Patented design allows adjustment to be carried out accurately (under load). No need to jack vehicle.

- A. From engine bay, loosen the '3' top nuts for strut tower upper mount.
- **B.** Use large screwdriver to lever / ratchet KMAC adjuster mount crossways for CAMBER, then lengthways for required CASTER.
- C. Once optimum settings, tighten the 'TOP' KMAC NUTS to 27Nm (20ft/lbs).



FRONT #193416-3L STAGE 3 (FULL RACE) BMW E34 '5' incl. 'M', E32 '7'

FRONT CAMBER (and CASTER) FOR THE 1st TIME (and accurate-underload direct on alignment rack)

STAGE 3 Solid - No elastomer / flex for Tauter, quicker response times

- KMAC not steel or soft billet alloy but ultimate highest aircraft 7075 grade aluminum and no mods to fit
- Biggest Adjustment Up to race winning 2.5°'s Neg. Camber Incl. "top coil seats" in OEM diam. & Coil overs (60-70 I.D.)
- Quickest Adjustment Change Camber & Caster settings Street/Race from engine bay and with strut brace fitted
- Centers "extra" H/Duty Self Align Spherical Bearings (PTFE Lined) Replaceable
- Steering Loads Separate H/Duty fully sealed radial thrust bearings and preventing spring drag / binding

· Always 1st With The Latest Design Breakthroughs

- 1. WISHBONE: Precise Ball Joint Adjustment System.
- 2. STRUT(top): Biggest/Quickest Adjustment System.
- 3. BUSHINGS: Single Wrench Precise On Car Adjustment.

Including unique KMAC "non-slip" lock system!

- Actual Inventors/Patentee's - The '3' Basic Suspension Systems —

We do appreciate any ideas to further improve our market leadership!